




技术参数	气动柱塞泵										插桶泵				转换泵				
																			
描述	P10	P10/1H	P30/1H	P30/2H	P80/1H	P80/2H	P80/2H-SV		P200/1H	P200/2H	P200/2H-SV	P200/2H-H		TP20	TP60	TP200	TP200	FP300	
性能/消耗																			
压力比	11:1 / 37:1	11:1 / 37:1	33:1		56:1		56:1		22/48/56:1	22/48/56/75:1	48:1 / 75:1	6.4:1			21:1		7.6:1	11:1/23:1/37:1	
流速 (L/min) 每20次往复	0.29 / 0.095	0.29 / 0.095	0.64		0.614		0.614		0.6 / 3	0.6 / 3 / 6	3 / 6	3 / 6			0,8		2,24	6	
最大粘度 (mPa·s)	0.2 / 0.5 百万	0.2 / 0.8 百万	2.5 百万		2.5 百万		5.0 百万		2.5/5.0 百万	2.5/5.0 百万	5.0 百万	5.0 百万			50,000		50,000	50,000	
最大工作压力 (bar)	160 / 250	160 / 250	250		315		315		250 - 400	250 - 400	250 - 400	250 - 400			160		80	250	
工作压力 (bar)	20 - 160	20 - 160	20 - 160		20 - 250		20 - 250		20 - 250	20 - 250	20 - 250	20 - 250			100		40	160	
空气消耗量 (L/min) 每20次往复/6bar	22	22	142		220		220		220 - 900	220 - 1,400	220 - 1,400	50			142		142	450/900/1,400	
尺寸/重量																			
启动气缸高度 (mm)	870	777	1,056		1,400		1,580		1,650		1,650	1,850	917	1,150	1,438		1,040		
延伸高度 (mm)	1,100	1,127	1,540		2,200		2,380		2,600		2,700	2,600	-	-	-		-		
底盘尺寸 长x宽 (mm)	250x310	410x300	610x500		610x500		750x550		900x600		1,000x750	910x1,000	-	-	-		-		
泵尺寸 (mm)	280	280	430		525		525		525 / 865		865	865	339	577	860		600		
重量 (不含包装箱) (kg)	175	22	60/67		75		90		205 - 240		350	380	16	16	16		38 / 42 / 46		
包装最大高度 (mm)	400	340	450		750		750		880		880	880	339	577	860		-		
包装箱容量 (L)	10	10	30		80		80		200		200	200	20	60	200		-		
包装箱最大外径 (mm)	315	315	455		444		440		575		575	575	339	577	860		-		
内径尺寸 最小/最大 (mm)	40 - 51	40 - 51	-		-		-		-		-	-	-	-	-		-		
设备																			
材料桶输送装置 或泵底座滚轮装置	-	-	-		-		-		○	○	○	○			-		-		
底盘定位 装置	-	-	●		●		●		●	●	●	●			-		-		
水平监测	-	○	○		○		○		○	●	●	●			-		-		
换包装桶水平监测 带自动关闭 和警报装置	-	●	●		●		●		●	●	●	●			-		-		
无障碍物料供应	-	○	○		○		○		○	●	○	○			-		-		
压盘	○	○	○		○		○		○	○	○	○			-		-		
不锈钢 易损件	○	○	○		○		○		○	○	○	○			○		○		
抗磨损 易损件	○	○	○		○		○		○	○	○	○			-		-		
制动润滑装置	-	-	-		○		○		-	-	-	-			-		-		
接口信号 (24V)	-	○	○		○		○		○	○	○	●			-		-		
单手操作	-	●	●/-		●/-		-		-	-	-	-			-		-		
双手安全操作	-	-	-/●		-/●		●		●	●	●	●			-		-		
ATEX / UL	○	○	○		○		○		○	○	○	○			○		○		

符号说明

- = 标准件
- = 可选件
- = 无
- SV = 大型升降气缸
- H = 液压
- * = 往复次数取决于粘度
- 1 bar = 14,5 psi / 0,1 MPa

All pumps confirm to CE



中国总部
德派 (上海) 计量科技有限公司
上海市闵行区合川路3089号A栋4楼A室
电话: +86 21 3368 7776
传真: +86 21 3368 7778
office@dopag.cn
www.dopag.cn

定量 · 混胶 · 涂胶

